

HITEMP PUMP SWITCH



OVERVIEW

Mechanically-activated, wide-angle switch specifically designed for performance and dependability in high temperature sump applications up to 200°F (93°C). This mechanically activated, wide-angle pump switch provides automatic control of pumps in water and sewage applications.

The HiTemp pump switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.

FEATURES

- Mechanically-activated, snap action contacts
- High impact, corrosion resistant, polypropylene float housing
- Adjustable pump range of 8 to 36 inches (20 to 91 cm)
- Twin wall design of float housing (patent pending) protects internal components from heat and moisture

OPTIONS

- Pump down applications
- 125 VAC or 250 VAC models
- With or without a piggy back plug
- In standard cable lengths 20 or 30 feet and 6 or 10 meters (longer lengths available)

MODELS AVAILABLE

- 20HTDWOP
- 30HTDWOP

SPECIFICATIONS

- **Cable:** flexible 16 guage, 2 conductor (UL, CSA) SJOOW, water-resistant, (CPE)
- **Float:** 3.18 inch diameter x 5.58 inch long, (8.1 cm x 14.2 cm), high impact, corrosion resistant, polypropylene housing for use in water up to 200°F (92°C)
- **Maximum Water Depth:** 33 feet (10 meters) or 13 PSI (90 kPa)
- **Electrical:**

125 VAC 50/60Hz Single Phase:

- Maximum Pump Running Current: 13 Amps
- Maximum Pump Starting Current: 78 Amps

250 VAC 50/60Hz Single Phase:

- Maximum Pump Running Current: 13 Amps
- Maximum Pump Starting Current: 78 Amps

Note: This switch is not recommended for controlling:

- Electric loads less than 100 milli-amps, 12 VAC
- Non-arcing electric loads

Note: This switch must be used with pumps that provide integral thermal overload protection.



844-4PRIMEX (477-4639)
WWW.PRIMEXCONTROLS.COM

Ashland, OH	800-363-5842
Clearwater, FL	800-349-1905
Detroit Lakes, MN	888-342-5753
Milford, OH	513-831-9959
Plymouth, MN	763-559-0568